

# HSK-M

Item number 1609250051LF



## Technical data

<b>Material</b>	Nickel-plated brass (lead-free)
<b>Clamping insert</b>	Polyamide VO according to UL94
<b>Seal</b>	NBR
<b>Material o-ring</b>	NBR
<b>Protection class</b>	IP68 - 10bar/30min , IP 69 K
<b>Type Rating by</b>	4 , 4X , 6 , UL 50E
<b>Temperature range</b>	-40 °C to +100 °C
<b>Variant</b>	Metric
<b>External thread (AG)</b>	M25 x 1,5
<b>Cable diameter</b>	9 - 16 mm
<b>Thread length (GL)</b>	7 mm
<b>Height (H)</b>	26 mm
<b>Wrench size (SW1/SW2)</b>	30/30 mm
<b>Tightening torque</b>	12 Nm



# HSK-M

Item number 1609250051LF

## Commercial data

Packaging Unit	25
EAN code	4033878014592
Weight	0.05844 kg
ETIM 7	EC000441
ETIM 8	EC000441
ETIM 9	EC000441
eCl@ss 10.1	27-14-44-32
Customs tariff number	74198090

Note:



Dimensions and specifications may be changed without prior notice

[www.hummel.com](http://www.hummel.com)