


# HSK-M-EMC-Ex

Item number 1616120050



## Technical data

<b>Material</b>	Nickel-plated brass
<b>Clamping insert</b>	Polyamide VO according to UL94
<b>Seal</b>	NBR
<b>Material o-ring</b>	NBR
<b>Protection class</b>	IP68 - 10bar/30min , IP 69 K
<b>Ex-protection level</b>	II 1D Ex ta IIIC Da , II 2G Ex eb IIC Gb
<b>Type Rating by</b>	4 , 4X , 6 , UL 50E
<b>Temperature range</b>	-20°C to +95°C
<b>Variant</b>	Metric
<b>External thread (AG)</b>	M12 x 1,5
<b>Cable diameter</b>	3 - 6,5 mm
<b>Thread length (GL)</b>	6.5 mm
<b>Height (H)</b>	19 mm
<b>Wrench size (SW1/SW2)</b>	14/14 mm
<b>Tightening torque</b>	4 Nm



# HSK-M-EMC-Ex

Item number 1616120050

## Commercial data

Packaging Unit	50
EAN code	4033878431603
Weight	0.01111 kg
ETIM 7	EC000441
ETIM 8	EC000441
ETIM 9	EC000441
eCl@ss 10.1	27-14-44-34
Customs tariff number	85369010

Note:

