

HSK-MZ-EMC-PVDF-Ex

Item number 1667380070



Technical data

| | |
|-----------------------|--|
| Material | Nickel-plated brass |
| Clamping insert | PVDF |
| Seal | FKM |
| Material o-ring | FKM |
| Protection class | IP68 - 10bar/30min , IP 69 K |
| Type Rating by | 4 , 4X , 6 , UL 50E |
| Ex-protection level | II 1D Ex ta IIIC Da , II 2G Ex eb IIC Gb |
| Temperature range | -20°C to +130°C |
| Variant | NPT |
| External thread (AG) | NPT 3/8" |
| Cable diameter | 4 - 8 mm |
| Thread length (GL) | 15 mm |
| Height (H) | 27 mm |
| Wrench size (SW1/SW2) | 17/19 mm |
| Tightening torque | 6 Nm |



HSK-MZ-EMC-PVDF-Ex

Item number 1667380070

Commercial data

| | |
|-----------------------|---------------|
| Packaging Unit | 50 |
| EAN code | 4033878438787 |
| Weight | 0.024 kg |
| ETIM 7 | EC000441 |
| ETIM 8 | EC000441 |
| ETIM 9 | EC000441 |
| eCl@ss 10.1 | 27-14-44-34 |
| Customs tariff number | 85369010 |

Note:



Dimensions and specifications may be changed without prior notice

www.hummel.com